


ZBench IMPACTII



















Technical specifications


- Mobile soundproofing table for GC/LC-MS with structure in high resistance aluminum profile.
- 13 mm HPL for the cladding and 20 mm thick Fundermax Resistance for the work surface, both with resistance to chemical products.
- Four lifting wheels with integrated fixing feet for greater stability.
- Supports a weight of up to 500 Kg.

Noise enclosure for 1 vacuum pump

- A lockable door for easy access to the vacuum pump for oil change.
- Compartment with 50 mm thick multi-layer acoustic insulation designed to soundproof motors, compressors and vacuum pumps. Reduces more than 85% of noise perception.
- **Anti-vibration system**: a stainless-steel tray with silent blocks to absorb the vibrations produced by the vacuum pump.













Ventilation system and access for pipe




 4 ultra-quiet, long-lasting (150.000 hours) and easily replaceable fans.




- 3 flexible plastic desk grommets for vacuum pump tubes and 2 flexible plastic desk grommets for drain tubes.
- 12V-5A power supply to connect to the 230V/50Hz network with safety connector.

Power switch and temperature alarm against overheating

 If a temperature higher than that recommended by the pump manufacturer is reached inside the noise enclosure, a red LED lights up and an acoustic signal is activated.









www.zenbench.es



Dimensions of ZBench IMPACTII	Width (cm)	Depth (cm)	Height (cm)
External dimensions of bench	120	88	55
Internal dimensions of noise enclosure	54	66	40



Compatibility with the main brands on the market

	Compatibility guide for ZBench-IMPACTII		
1	TECHNIQUE	BRUKER	
	MS	IMPACTII COMPACT	



